

Special forestry

Product Information Sheet

DESCRIPTION Extruded polypropylene tube which protects and helps establish trees

APPLICATION For the protection of trees against animal browsing, herbicide spray and for the improvement of growth through a microclimate

SECTORS Forestry and horticulture

Twin wall; best strength to weight ratio



UV stabilised; provides minimum 5 year protection



Strengthening rods; prevents shelter tearing at stake area



Flared rim; minimises stem abrasion



Translucent green; maximises light transmission for photosynthesis



Laserline; shelter splits avoiding strangulation as tree grows

		TUBEX Special forestry				
Dimensions						
Height	m	0.4	0.5	0.6	0.9	1.20
Diameter	mm	77–100	77–100	77–100	77–100	77–100
Av. Weight per tube	g	51	64.5	76.5	115	153
Packaging		For all sizes				
Nest		5				
Bundle		100				
Bag or strap banded		Bag				

Material	For all sizes
Tube	Polypropylene
Colour	Green
Service Life	Minimum 3 years
Degradability	Photodegradable
Manufacturing tolerance	- 25mm
Recommended support	Cane / Stake

As part of its continual improvement process Fiberweb Geosynthetics Ltd reserve the right to change the properties listed on this data sheet without prior notice.

TM indicates a trade mark of Fiberweb plc or a Fiberweb Group company, many of which are registered in a number of countries around the world.